## Autofill Countertop 20L With Built in Filtration


| Product Code    | 069788                   |
|-----------------|--------------------------|
| Model no.       | AFF20CT                  |
| EAN Barcode     | 5011139069788            |
| Product type    | Autofill Boiler          |
| Warranty Period | 2 years parts and labour |



## **Water Boiler Features**

- Replaceable water filter provides better tasting beverages and reduces limescale buildup.
- Desired water temperature can be easily set between 98°c down to 70°c for more delicate speciality teas.
- Will dispense upto 206 cups per hour / 31 litres, with 22 litre rapid draw-off.
- The boilers eco-mode can be programmed to suit the location, reducing running costs and saving energy.
- Robust chrome tap, can be switched between controllable and constant flow with 219mm tap height above tray.
- Large capacity water tank perfect for busy locations
- Tough plastic drip tray, easy to empty and clean, with drain outlet for optional waste water connection.

## Dimensions (mm)



| Technical Information              |   |  |
|------------------------------------|---|--|
| Product Info:                      |   |  |
| Filtered                           | Yes                                     |  |
| Capacity (litres)                  | 20                                      |  |
| Packed Dimensions (WxDxH, mm)      | 432x490x773                             |  |
| Drip Tray Dimensions (WxDxH, mm)   | 344x195x50                              |  |
| Product Weight (kg)                | 11.7                                    |  |
| Packed Weight (kg)                 | 14.7                                    |  |
| Colour                             | Bright Annealed Stainless Steel & Black |  |
| Body Construction / Material       | 430 Stainless Steel                     |  |
| Tank Construction / Material       | 304 grade Stainless Steel               |  |
| Trim and drip tray plastic type    | PC ABS                                  |  |
| Tap Material type                  | Chrome                                  |  |
| Dual Function Tap                  | Yes                                     |  |
| Safety Standards test              | EN60335                                 |  |
| Nonslip Feet                       | Yes                                     |  |
| Boil Dry cut-out                   | Yes                                     |  |
| Performance:                       |   |  |
| Heat up Time to 98°c (minutes)     | 56                                      |  |
| Rapid Draw off—Litres              | 22                                      |  |
| Rapid Draw off—Pints               | 39                                      |  |
| Rapid Draw off—Cups                | 146                                     |  |
| Output per Hr—Litres               | 31                                      |  |
| Output per Hr—Pints                | 55                                      |  |
| Output per Hr—Cups                 | 206                                     |  |
| Recovery Per min—Litres            | 0.5                                     |  |
| Recovery Per min—Pints             | 0.88                                    |  |
| Recovery Per min—Cups              | 3.3                                     |  |
| Heat up time 70°c−98°c (minutes)   | 16                                      |  |
| Cool down time 98°c—70°c (minutes) | 596                                     |  |
| Standard power consumption (kW/hr) | 0.12                                    |  |
| Installation:                      |   |  |
| Hard wiring required               | No                                      |  |
| UK fitted plug                     | Yes                                     |  |
| Cable length (m)                   | 1.5                                     |  |
| Water feed pipe length (m)         | 2                                       |  |
| Max. water inlet pressure (bar)    | 8                                       |  |
| Element power rating               | 2.8                                     |  |
| Phase type                         | Single                                  |  |
| Nominal voltage                    | 230V 50-60Hz                            |  |
| Electrical supply current (A)      | 13                                      |  |
|                                    |   |  |



Water inlet connection fitting

3/4" BSP