



# Product Code: FMSLIM1200NG 18-153

## 1200mm Slimline multideck with nightblind and glass end panels

---



### Features & Benefits

---

- Optimum storage and display from the smallest possible footprint
- Energy saving LED lighting is brighter, lasts longer and saves you money
- Additional shelf depth (400mm) delivers increased volume compared to competitor slimline cabinets
- Extra wide glass end panels increase display visibility
- Add 60mm to depth for spacer if product is to be wall-sited (required for air circulation - detachable if not wall sited)
- 1x top mounted full length LED. On average these last 10x longer than fluorescent lighting and emit a fraction of the heat output.
- Energy saving retracting 'Soft Closing Mechanism' Nightblind.
- Fully removable shelves and supports for ease of cleaning.
- Made of high quality food safe superior 'brushed' stainless steel finish for easy wipe-clean efficiency.
- Removable front cover and slide out condensing unit allows easy access for service, minimising down time. Also our After Sales Support is there when you need us: 2 years parts and labour warranty as standard.

## Refrigeration

<b>R290 - Energy Efficient</b>	Standard
<b>Integral Refrigeration System</b>	Standard

## Specification

<b>M2 Temp +2/+4°C</b>	Standard
<b>Width (mm)</b>	1195
<b>Depth (mm)</b>	680
<b>Height (mm)</b>	1780
<b>Unpacked weight (Kgs)</b>	190
<b>Packed weight (Kgs)</b>	211.14

## Electrical & Service Data

<b>230/50/1</b>	Standard
<b>Fuse Required (A)</b>	10

## Finish

<b>304 s/s ext &amp; int</b>	Standard
------------------------------	----------

## Product Extras

<b>Additional S/S shelf and support brackets</b>	Option
<b>Front wire baskets for additional storage</b>	Option

## Energy

<b>TDA (m2)</b>	2.29
<b>Max-Min temp (of stored product)</b>	+7°C / -1°C
<b>Climate class</b>	3
<b>kWh (24 hours)</b>	23.8
<b>AEC</b>	8702
<b>Energy Grade</b>	F
<b>Energy Efficiency Index</b>	79.4

## Footnotes

- Allow 60mm spacer if product is wall-sited (required for air circulation). Spacers are detachable if product is not to be wall-sited
- Delivery to dealer premises/direct to site on route days free of charge. Delivery and installation to ground floor site as priced - see UK price list for conditions
- Performance complies with M2 classification as prescribed in EN23953-2:2005. M2 refers to product temperatures of no greater than +7°C and no lower than -1°C when loaded in accordance with the standard and recorded under test conditions.

# Energy Performance Data and information




Foster Refrigerator

FMSLIM1200NG  
(18-153)



**8702** kWh/annum

  
**2.29** m<sup>2</sup>

 **7°C**  
**-1°C**

2021/745

## Application

This appliance is intended for use in ambient temperatures up to 40°C

## Safety

Precautionary instructions and maintenance advice, to ensure efficient operation, can be found in this products operating instructions.

## Recycling

For recycling and end of life care for this product, please refer to environmental section of the website or visit [our policies](#)



The Refrigeration Experts

All images shown are for illustration purpose only. All images and photographs are not intended to be relied upon for, nor to form part of, any contract unless specifically incorporated in writing into the contract. Solely the dimensions and specifications incorporated in the quotation or purchase order confirmation shall be contractually binding.