



# BOXER SERIES



## BOXER 42



Standard  
1 x 420 mm  
seal



Option  
2 x 420 mm  
seal

- Capacity pump 0.21 m<sup>3</sup>/h
- Machine cycle 15-35 sec.
- Dimensions (l x w x h) 520 x 480 x 450 mm
- Weight 62 kg
- Voltage 230V-1-50 Hz (Other voltages available)
- Power 0.75 - 1.0 kW

Pure  
Vacuum

## BOXER SERIES

### FAST AND ROBUST VACUUM PACKAGING MACHINES WITH WORLD WIDE REPUTATION

- Durable and efficient high quality table models
- Complete range for vacuum and MAP packaging solutions
- Extensive program choices for specific packaging requirements
- Fully HACCP compatible with optional labelling device
- Hygienic and Intelligent Design
- User friendly and low maintenance, supplied with complete service program

### FOOD PRODUCTS

Retail Trade - Restaurants - Catering - Supermarkets  
(meat, poultry, fish, cheese, vegetables etc.)

- No contamination or bacteria's multiplication, hence an extended shelf life resulting in:
  - cost savings (larger purchasing orders, efficient cooking time spreading and diminution of products losses)
  - turnover increase (more variation and spread in product range)
- Optimal product and storage hygiene (hermetically sealed)
- No loss of product (prevents drying out, moulds and freeze burn)
- Improved product quality (product maturing in packaging, no loss of aroma)
- Professional product presentation
- Optimal packaging contributes to food safety and HACCP standards
- Ideal for Sous-vide Cuisine applications

### NON-FOOD PRODUCTS

Electronics - Semi-conductors - Metal - Pharmaceutical Products - Textiles - Laboratories etc.

- Moisture free packaging
- Air and dust free packaging
- Volume reducing packaging
- Scrapes and scratches free solution
- Fraud resistant packaging
- Sterile and contamination free packaging
- Antistatic packaging (ESD)

## SPECIFICATIONS

### GENERAL

- Table model
- Stainless steel housing
- Stainless steel deep-drawn vacuum chamber for optimal hygiene
- Transparent lid
- Easily removable wireless sealing bars in vacuum chamber
- Insert plates for adjusting vacuum chamber height

### PACKAGING FUNCTIONS

- **Vacuum**  
Optimal final vacuum 99,80% (2 Mbar)
- **Gas-flush**  
Injecting food-gas for product protection and longer shelf life
- **Soft-air**  
Controlled ventilation for protection of product and packaging

### SEALING SYSTEMS

- **Double Seal**  
2 x 3,5 mm convex sealing wires for product remains elimination and strong hermetic seals.
- **Cut-off seal**  
1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / One time setting (cut off remaining flap)
- **1-2 Cut-off seal**  
1 x 3,5 mm convex sealing wire + 1 x 1.1 mm round cutting wire / Independent time setting (shrink bags)
- **Wide Seal**  
1 x 8.0 mm flat sealing wire
- **Bi-Active Seal**  
Upper and lower sealing bars with 1 x 5.0 mm flat sealing wire (thick and aluminium vacuum bags)  
(only applicable to the Boxer 42 XL Bi-active and ESD models)

### OPERATIONAL CONTROL FUNCTIONS

- **Digital Control**  
Time control / Automatic programming / 10 default programs
- **Sensor Control**  
Set percentage pressure for vacuum and gas functions for accurate and constant packaging results / Automatic programming / 10 default programs / Vacuum plus time
- **Liquid Control**  
Set percentage pressure for vacuum and detect boiling point of the product. For fast cycle and better food protection
- **Advanced Control System**  
Set percentage pressure or mbar/hPa for vacuum and gas function for accurate and constant packaging results / 20 default alphanumeric programs / Vacuum plus time / Sequential vacuum / Secured Operator Access / HACCP track and trace function / LCD full color screen / PC interface / Compatible with label printer

### SUPPORT CONTROL FUNCTIONS

- STOP button for partial/full cycle interruption
- Digital maintenance program for pump / Operating hours counter / Service indicator programs / Sleeper function etc.

### OPTIONAL FUNCTIONS / ACCESSORIES

- Inclined insert plate for packaging liquid products
- Compact label printer (Zebra Technologies)
- Connector for external vacuuming of food containers
- Service kit for standard maintenance
- Trolley with shelves and castors



Option Standard

Sentence and printing errors reserved