



KPS 42 CH

Product series: KP - KPS

Item number: 865780554

KPS 42 CH is a blast chiller featuring innovative technological solutions offering high food safety and performance. And with the new intuitive controller it has never been easier to manage chilling cycles.

Featuring

- Self closing door
- Removable support for 1/1 GN and 40 x 60 cm,
- Multipoint probe with 3 measuring points,
- Choose either the IFR operation, time or temperature controlled chill cycle.
- Prevent surface freezing damage with the IFR blast chilling function.
- Up to 20 customized cycles can be stored.
- HACCP alarms
- Operates as a storage cabinet after the chilling process has finished.

height: 1850 mm

Exterior / interior: Stainless / Stainless

Temperature range: 0 ° C / + 10 ° C.

Cooling capacity: 45 kg from + 70 ° C to + 3 ° C in 90 minutes.



SPECIFICATIONS

Connection	400V 3N 50Hz or 230V, 50/60Hz	Connection load (Watt)	2000
Insulation	75 mm (cyclopentane)	Sound level – dB(A)	72
Temperature range	0/+10°C	Refrigeration capacity at -10°C (Watt)	2245
Exterior	Stainless	Climate class	e
Interior	Stainless	Refrigerant (kg)	2
Dimensions W x D x H (mm)	800 x 830 x 1850	CO2 equivalent (kg)	4282
Weight, packed (kg)	200	Energy consumption - Chilling (kWh/kg)	0.09
Refrigerant	R452A	Please observe	This model is available as a single phase unit. 230 V, 50 Hz - 30 amp fuse
GWP	2141	Chilling capacity (from +70°C to +3°C in 90 minutes)	36 kg from +70°C to +3°C in 90 min.