

GGPv 1490

ProfiPremiumline



Total gross capacity	1427 litre
Ext. dimensions in mm (w/d/h)	1430/830/2150
Int. dimensions in mm (w/d/h)	1240/650/1550
Energy consumption in 24 h	12,490 kWh
Climate rating ¹	T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	-10°C to -26°C
Gastronorm	530 x 650 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	304-grade stainless steel
Type of control	electronic with text display
Temperature display	external digital
Interior light	_
Fault: warning signal	visual and audible
Interface	RS 485
volt-free alarm contact	yes
Shelves	9
Adjustable Shelving	-
Number of drawers	-
Number of baskets	-
Maximum number of baskets	-
Shelf material	grid shelves with 304-grade stainless steel
Shelf loading	60 kg
Height of adjustable legs	120-170
Castors/type of castors	_
Door handle	full-length integrated door handle
Foot pedal opener	yes
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	-
Refrigerant	R 290
Airborne acoustical noise emissions	60 dB(A)
Gross/net weight	225/201 kg
EAN-Nr.	9005382169933

Subject to modification. Timestamp: 10.02.2016

•

 $1 \quad \text{Climate Ratings: } \textbf{SN} + 10^{\circ} \text{C to } + 32^{\circ} \text{C} \qquad \textbf{N} + 16^{\circ} \text{C to } + 32^{\circ} \text{C} \qquad \textbf{ST} + 16^{\circ} \text{C to } + 38^{\circ} \text{C} \qquad \textbf{T} + 16^{\circ} \text{C to } + 43^{\circ} \text{C}$

•

