GGv 5060

Total gross capacity	478 litre
Ext. dimensions in mm (w/d/h)	750/750/1864
Int. dimensions in mm (w/d/h)	610/500/1225
Energy consumption in 24 h	3,410 kWh
Climate rating[1]	SN-T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	-14°C to -28°C
Gastronorm	600 x 400, 530 x 325 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	moulded polystyrol white
Type of control	electronic controller
Temperature display	external digital
Interior light	–
Fault: warning signal	visual and audible
Interface	–
volt-free alarm contact	–
Shelves	5
Adjustable Shelving	–
Number of drawers	–
Number of baskets	–
Maximum number of baskets	–
Shelf material	grid shelves plastic-coated
Shelf loading	60 kg
Height of adjustable legs	150-180
Castors/type of castors	–
Door handle	stainless steel door handle
Foot pedal opener	–
Self-closing door	yes
Insulation	70 - 70 mm
Defrost water drain	–
Refrigerant	R 290
Airborne acoustical noise emissions	55 dB(A)
Gross/net weight	108/100 kg
EAN-Nr.	9005382167656

Subject to modification. Timestamp: 11.02.2016

1 Climate Ratings: **SN** +10°C to +32°C **N** +16°C to +32°C **ST** +16°C to +38°C **T** +16°C to +43°C

LIEBHERR