



### PRODUCT OPTIONS AND ACCESSORIES

- OA8902 SPLASHBACK/SHELF

### PRODUCT FEATURES

- Powerful 6kW burners - the pan will heat up quicker, speeding up processes such as boiling and sautéing, achieving a caramelised colour faster
- Fully pressed hob - Simpler and quicker to clean
- Twin heavy-duty cast iron supports, built to withstand the rigours of the busiest kitchen
- Low flue, hob top accommodates larger pans
- Powerful 6kW twin fan assisted oven for more even cooking. Large 4 x GN1/1 capacity enabling four different foods to be cooked simultaneously
- 2 shelves and 5 shelf positions maximise oven space
- Castors supplied as standard, not as a chargeable extra



# LINCAT PHOENIX DUAL FUEL PROPANE GAS FREE-STANDING OVEN RANGE - 6-ZONE - W 900 MM - 36 KW [GAS] - 6 KW

## MODEL: PHDR01/P

### WEIGHTS & DIMENSIONS

Width	900 mil
Depth	800 mil
Height	900 mil
Weight	125 kg

### SHIPPING DETAILS

Ship Width	100 cm
Ship Depth	85 cm
Ship Height	105 cm
Ship Weight	137.5 kg
Ship Method	LTL Common Carrier
Shipping Package Type	Pieces
Shipping Origin Zip Code	LN6 3QZ, UNITED KINGDOM
Quick Ship Product	No

### PRODUCT CERTIFICATIONS



### ENERGY SPECS

Primary Energy Type	Dual Fuel (residential only)	Electrical Connection Type	Direct Hardwired
Electrical Amps Per Conductor	Single Phase 26.1/Three Phase L1=8.7; L2=8.7; L3=8.7	Number of Electrical Conductor Wires	1
Electrical Total Amperage	26.1 A	Dedicated Circuit Required	No
Electrical Volts	230-400V	Electrical Remarks	Single, Three
Electrical Total Wattage	6000 W	Gas Type	Propane
Electrical Kilowatts	6 kW	Gas Total BTUs	122832 BTU
Electrical Plug Type	Hardwired	Gas Inlet Size	0.75 in
Number of Electrical Plugs	Not Applicable	Gas Inlet Pressure Required	37 mBar
		Gas Consumption at Max Use Per Hour	2.58 m <sup>3</sup>
		Total Heat Input at Max Use	36 Kw, 122832 BTU per hour

Lincat reserves the right to modify specifications or discontinue models without incurring obligation. Dimensions nominal.

Document Auto-Generated  
March 25, 2025



**LINCAT PHOENIX DUAL FUEL PROPANE GAS FREE-STANDING  
OVEN RANGE - 6-ZONE - W 900 MM - 36 KW [GAS] - 6 KW**

**MODEL: PHDR01/P**

**ADDITIONAL SPECIFICATIONS**

Construction Materials	Stainless Steel	Open or Sealed Burners	Sealed
Control Type	Rotary Control Knob	Oven Power Rating	6 kW
Cooking Plate Finish Material Type	Cast Iron Plate	Oven Temperature Minimum	40 °C
Exterior Trim Finish Color	Stainless Steel	Oven Temperature Maximum	250 °C
Gastronorm Capacity	4 x GN1/1	Shelf Depth	512 mm
High Altitude Kit Available	No	Shelf Width	710 mm
Number of Heating Zones	6	Ventless Cooking Technology	No
Number of Hot Top Burners	6	Cooking Equipment	Sealed Burner
Number of Shelf Positions	5	BTUs Per Burner	6 KW
Number of Shelves	2		

SELECT COOKING EQUIPMENT	NUMBER OF	POWER RATING	ARRANGE- MENT	WIDTH	DEPTH	
Sealed Burner 1		6	6	Center	300 mm	300 mm

SELECT BASE EQUIPMENT	NUMBER OF	CUBIC CAPACITY EACH	WIDTH	DEPTH	HEIGHT
Standard Oven 1		1	715 mm	530 mm	400 mm

**BIDDING SPECIFICATIONS (SHORT FORM SPECS)**

Bidding Specifications Not Available.



TECHNICAL DRAWING

